4

RW No. 5, January 2012



National Committee on Uniform Traffic Control Devices

National Committee on Uniform Traffic Control Devices

RWSTC RECOMMENDATION FOLLOWING SPONSOR COMMENTS

TECHNICAL COMMITTEE: NCUTCD Regulatory/Warning Signs Technical

DATE OF ACTION: (TASK FORCE): 6-5-11, 1-7-12 REVISED FOLLOWING

TOPIC: Design of parking signs R7-21 and R7-21a Add sign codes to text (NPA

AFFECTED PORTIONS OF MUTCD: Section 2B.47 and Figure 2B-24 (2009)

12615 West Keystone Drive * Sun City West, AZ, 85375 Telephone (623)680-9592 * e-mail: ncutcd@aol.com

5 6

7

8

9

10

11

12

13

14

15

16

SPONSOR COMMENTS, revised 1-9-12, revised 1-18-12 17 TASK FORCE: Tom Heydel (chair), Randy McCourt, Dan Paddick, Ron Lipps,

Jim Pline, Fred Ranck 18

19 **RWSTC APPROVAL DATE: 6-23-11**

20 TRANSMITTAL TO SPONSORS DATE: Fall 2011 21 RWSTC APPROVAL DATE FOLLOWING SPONSOR COMMENTS: 1-18-12

22 23

24 25

26 27

28 29

34 35

33

36

37

38 39

40 41

MUTCD) 30 **BACKGROUND:** 31 As part of the review of the NPA council approved Section 2B.54 (NPA) which 32 became section 2B.47 in the 2009 MUTCD with some modifications recommended. The

versus 2009 MUTCD)

Committee

DISCUSSION:

Signs R7-21 and R7-21a are shown in figure 2B-24 but within the text the sign code

is needed to be referenced. Add sign codes to text.

compared to the NPA makes the following recommended changes.

COUNCIL APPROVAL DATE: 1-19-12

Also, the R7-20 Pay station sign that is placed at the pay station often has a color coding based on the number of hours. The 2009 MUTCD says that all parking signs

2009 MUTCD made some changes to the NPA and FHWA did not follow some of the

recommendations by NCUTCD Council vote. In its review of the 2009 MUTCD as

42 color coding are to be green, red or black for time limits. By adding an option statement 43 that says the R7-20 sign can be other colors then green, it allows for this color coding of 44 the portion of the sign where the 1 hour, 2 hour, 3 hour, etc is shown. The rest of the sign 45 would be green/white. 46 47 **RECOMMENDATION:** 48 49 Note: Proposed changes to the MUTCD are shown in underline red and removed 50 text are shown in strikethrough red. 51 52 RECOMMENDED WORDING to the 2009 MUTCD 53 54 Section 2B.47 Design of Parking, Standing, and Stopping Signs 55 Support: 56 01 Discussions of parking signs and parking regulations in this Section apply not only to 57 parking, but also to standing and stopping. 58 Standard: 59 02 The legend on parking signs shall state applicable regulations. Parking signs 60 (see Figures 2B-24 and 2B-25) shall comply with the standards of shape, color, 61 and location. 62 03 Where parking is prohibited at all times or at specific times, the basic design 63 for parking signs shall have a red legend and border on a white background 64 (Parking Prohibition signs), except that the R8-4 and R8-7 signs and the 65 alternate design for the R7-201aP plaque shall have a black legend and border 66 on a white background, and the R8-3 sign shall have a black legend and border 67 and a red circle and slash on a white background. 68 04 Where only limited-time parking or parking in a particular manner are 69 permitted, the signs shall have a green legend and border on a white 70 background (Permissive Parking signs). 71 72 05 Parking signs should display the following information from top to bottom of the sign, 73 in the order listed: 74 A. The restriction or prohibition; 75 B. The times of the day that it is applicable, if not at all hours; and 76 C. The days of the week that it is applicable, if not every day. 77 06 If the parking restriction applies to a limited area or zone, the limits of the restriction 78 should be shown by arrows or supplemental plagues. If arrows are used and if the sign is 79 at the end of a parking zone, there should be a single-headed arrow pointing in the 80 direction that the regulation is in effect. If the sign is at an intermediate point in a zone, 81 there should be a double-headed arrow pointing both ways. When a single sign is used at 82 the transition point between two parking zones, it should display a right and left arrow

pointing in the direction that the respective restrictions apply.

83

- 84 07 Where special parking restrictions are imposed during heavy snowfall, Emergency
- 85 Snow Route (R7-203) signs (see <u>Figure 2B-24</u>) should be installed. The legend will vary
- 86 according to the regulations, but the signs should be vertical rectangles, having a white
- 87 background with the upper part of the plate a red background.
- 88 Standard:
- 89 08 Where parking spaces that are reserved for persons with disabilities are
- 90 designated to accommodate wheelchair vans, a VAN ACCESSIBLE (R7-8P)
- 91 plaque shall be mounted below the R7-8 sign. The R7-8 sign (see Figure 2B-24)
- 92 shall have a green legend and border and a white wheelchair symbol on a blue
- 93 square, all on a white background. The R7-8P plaque (see Figure 2B-24) shall
- have a green legend and border on a white background.
- 95 Option:
- 96 on To minimize the number of parking signs, blanket regulations that apply to a given
- 97 district may, if legal, be posted at district boundary lines.
- 98 10 As an alternate to the use of arrows to show designated restriction zones, word
- 99 messages such as BEGIN, END, HERE TO CORNER, HERE TO ALLEY, THIS SIDE OF SIGN,
- or BETWEEN SIGNS may be used.
- 101 11 Where parking is prohibited during certain hours and time-limited parking or parking in
- a particular manner is permitted during certain other time periods, the red Parking
- 103 Prohibition and green Permissive Parking signs may be designed as follows:
- 104 A. Two 12 x 18-inch parking signs may be used with the red Parking Prohibition sign installed above or to the left of the green Permissive Parking sign; or
- 106 B. The red Parking Prohibition sign and the green Permissive Parking sign may be combined (see <u>Figure 2B-24</u>) to form an R7-200 sign on a single 24 x 18-inch sign, or an R7-200a sign on a single 12 x 30-inch sign.
- 109 12 At the transition point between two parking zones, a single sign or two signs mounted side by side may be used.
- 111 13 The words NO PARKING may be used as an alternative to the No Parking symbol. The
- supplemental educational plaque, NO PARKING, with a red legend and border on a white
- background, may be used above signs incorporating the No Parking symbol.
- 114 14 Alternate designs for the R7-107 sign may be developed such as the R7-107a sign
- (see Figure 2B-24). Alternate designs may include, on a single sign, a transit logo, an
- approved bus symbol, a parking prohibition, the words BUS STOP, and an arrow. The
- preferred bus symbol color is black, but other dark colors may be used. Additionally, the
- transit logo may be displayed on the bus face in the appropriate colors instead of placing
- the logo separately. The reverse side of the sign may contain bus routing information.
- 120 15 To make the parking regulations more effective and to improve public relations by
- 121 giving a definite warning, a TOW-AWAY ZONE (R7-201P) plaque (see Figure 2B-24) may
- be appended to, or incorporated in, any parking prohibition sign. The Tow-Away Zone
- (R7-201aP) symbol plaque may be used instead of the R7-201P word message plaque.
- 124 The R7-201aP plaque may have either a black or red legend and border on a white
- background.

1	2	~
ı	26	Guidance:

- 127 16 If a fee is charged for parking and a midblock pay station is used instead of individual
- parking meters for each parking space, pay parking signs should be used. Pay Parking
- 129 (R7-21 through R7-22) (R7-22) signs (see Figure 2B-24) should be used to define the
- area where the pay station parking applies. Pay Station (R7-20) signs (see Figure 2B-24)
- should be used at the pay station or to direct road users to the pay station.

132 Standard:

- 133 17 If the pay parking is subject to a maximum time limit, the appropriate time
- 134 limit (number of hours or minutes) shall be displayed on the Pay Parking (R7-21
- 135 or R7-21a) and Pay Station (R7-20) signs.
- 136 Option:
- 137 18 In rural areas (see Figure 2B-25), the legends NO PARKING ON PAVEMENT (R8-1) or
- NO STOPPING ON PAVEMENT (R8-5) are generally suitable and may be used. If a
- roadway has paved shoulders, the NO PARKING EXCEPT ON SHOULDER sign (R8-2) or
- the NO STOPPING EXCEPT ON SHOULDER sign (R8-6) may be used as these signs would
- be less likely to cause confusion. The R8-3 symbol sign or the word message NO
- PARKING (R8-3a) sign may be used to prohibit any parking along a given highway. Word
- message supplemental plaques may be mounted below the R8-3 or R8-3a sign. These
- word message supplemental plagues may include legends such as EXCEPT SUNDAYS &
- HOLIDAYS (R8-3bP), ON PAVEMENT (R8-3cP), ON BRIDGE (R8-3dP), ON TRACKS (R8-
- 3eP), EXCEPT ON SHOULDERS (R8-3fP), LOADING ZONE (with arrow) (R8-3gP), and
- 147 X:XX AM TO X:XX PM (with arrow) (R8-3hP).
- 148 19 Colors that are in compliance with the provisions of Section 2A.10 may be used for
- 149 color coding of parking time limits.
- 150 19 The Pay Station (R7-20) sign may contain colors other than green for color coding the
- parking time limit portion of the sign only.



R7-20

Note: Existing sign in 2009 MUTCD

154 Guidance:

- 155 20 If colors are used for color coding of parking time limits, the colors green, red, and
- 156 black should be the only colors that are used.

157

152

153

- 158 RWSTC VOTE 1-18-12:
- 159 For: 21
- 160 Opposed: 2 161 Abstentions: 2

162

163	COUNCIL VOTE: 1-19-12 For: 32 Opposed: 4 Abstentions: 0	
164		
165	c:ncutcd/January 2012 /Heydel/Section 2B.47 Design of parking signs R7-21 –	
166	comparison of NPA to 2009 MUTCD 6-5-11, revised 6-23-11, Revised 1-7-12, 1-9-12	
167	1-18-12 following sponsor comments, council approved 1-19-12	