



**National Committee on  
Uniform Traffic Control Devices**

17200 West Bell Road No.1135 \* Surprise, Ariz. 85374  
Telephone (623) 214-2403 \* e-mail: ncutcd@aol.com

RWSTC Agenda item III.2, January 2014

**National Committee on Uniform Traffic Control Devices  
RWSTC**

**TECHNICAL COMMITTEE: NCUTCD Regulatory/Warning Signs Technical  
Committee**

**DATE OF ACTION: (Task Force) 5-11-13**  
**TASK FORCE: Tom Heydel (chair), Jason Kennedy, Paul Carlson**  
**RWSTC APPROVAL DATE: 6-26-13, revised 12-16-13 following sponsor  
comments**  
**TRANSMITTAL TO SPONSORS DATE: December 2013**  
**RWSTC APPROVAL DATE FOLLOWING SPONSOR COMMENTS: 1-8-14**  
**COUNCIL APPROVAL DATE: 1-10-14**

**TOPIC: Table 2A-3, and Section 2A.08 - Added sheeting types - Minimum  
Maintained Retroreflectivity Levels**

**AFFECTED PORTIONS OF MUTCD: Table 2A-3, Section 2A.08**

**DISCUSSION/QUESTION:**

In April 2008, FHWA published “Minimum Retroreflectivity Levels for Blue and Brown Signs, Publication No FHWA-HRT-08-029. At the time the 2009 MUTCD was placed in the docket for comment, brown and blue signs did not have final approved research for minimum levels of retroreflectivity. Therefore, blue and brown background signs were excluded from retroreflectivity minimum standards in the 2009 MUTCD. This publication has those levels contained within table 17 (Minimum MR levels) of this document. The table was amended on July 5, 2011. ASTM D4956-11a is also shown on this table 17 at the top. The 2009 manual indicates ASTM D4956-04. The FHWA website under MUTCD and subheading publications has this FHWA-HRT-08-029 report with the update to the table 2A-3 related to brown and blue signs.

43 Also, since the time the 2009 MUTCD was published, prismatic sheeting type XI has  
 44 now been approved by FHWA and should be listed as well in table 2A-3. The rest of this  
 45 table mirrors table 2A-3 of the 2009 MUTCD.

46

47 **RECOMMENDATION:**

- 48 • Add prismatic sheeting type XI to table 2A-3.
- 49 • Change ASTM D4956-04 to read ASTM D4956-1 1a to the sheet type heading.  
 50 1a replaces 04.
- 51 • Eliminate the option statement regarding exclusion of blue and brown background  
 52 signs from the Section 2A.08 option statement.
- 53 • Add W21-1a worker sign to table 2A-3 to be consistent with the FHWA sign  
 54 details.

55

56

57 **RECOMMENDED WORDING:**

58 **Note:** Proposed changes to the MUTCD are shown in underline red and removed  
 59 text are shown in ~~strikethrough red~~.

60 **Section 2A.08 Maintaining Minimum Retroreflectivity**

61 Support:

62 01 Retroreflectivity is one of several factors associated with maintaining nighttime sign  
 63 visibility (see Section 2A.22).

64 **Standard:**

65 02 **Public agencies or officials having jurisdiction shall use an assessment or**  
 66 **management method that is designed to maintain sign retroreflectivity at or**  
 67 **above the minimum levels in Table 2A-3.**

Table 2A-3. Minimum Maintained Retroreflectivity Levels					
Sign Color	Sheeting Type ( <del>ASTM D4956-04</del> ) ( <u>ASTM D4956-11a</u> )				Additional Criteria
	Beaded Sheeting			Prismatic Sheeting	
	I	II	III	III, IV, VI, VII**, VIII, IX, X**, <u>XI</u>	
White on green	$W^*; G \geq 7$	$W^*; G \geq 15$	$W^*; G \geq 25$	$W \geq 250; G \geq 25$	Overhead
	$W^*; G \geq 7$	$W \geq 120; G \geq 15$			Ground mounted
<u>White on blue</u>	<u><math>W^*; B \geq 3</math></u>	<u><math>W^*; B \geq 5</math></u>	<u><math>W^*; B \geq 12</math></u>	<u><math>W \geq 250; B \geq 12</math></u>	<u>Overhead</u>
	<u><math>W^*; B \geq 3</math></u>	<u><math>W \geq 120; B \geq 7</math></u>			<u>Ground mounted</u>
<u>White on brown</u>	<u><math>W^*; Br \geq 1</math></u>	<u><math>W^*; Br \geq 5</math></u>	<u><math>W^*; Br \geq 10</math></u>	<u><math>W \geq 350; Br \geq 10</math></u>	<u>Overhead</u>
	<u><math>W^*; Br \geq 1</math></u>	<u><math>W \geq 150; Br \geq 5</math></u>			<u>Ground mounted</u>

Black on yellow or black on orange	Y*; O*	$Y \geq 50; O \geq 50$	①
	Y*; O*	$Y \geq 75; O \geq 75$	②
White on red		$W \geq 35; R \geq 7$	③
Black on white		$W \geq 50$	—

The minimum MR levels shown in this table are in units of  $cd/lx/m^2$  measured at an observation angle of  $0.2^\circ$  and an entrance angle of  $4.0^\circ$ .

① For text and fine symbol signs measuring at least 1,200 mm (48 inches) and for all sizes of bold symbol signs.

② For text and fine symbol signs measuring less than 1,200 mm (48 inches).

③ Minimum Sign Contrast Ratio  $\geq 3:1$  (white retroreflectivity  $\div$  red retroreflectivity).

\* This sheeting type should not be used for this color for this application.

\*\* this type sheeting was consolidated and has become type VIII sheeting under ASTM D4956-11a

#### Bold Symbol Signs

<ul style="list-style-type: none"> <li>W1-1, -2 – Turn and Curve</li> <li>W1-3, -4 – Reverse Turn and Curve</li> <li>W1-5 – Winding Road</li> <li>W1-6, -7 – Large Arrow</li> <li>W1-8 – Chevron</li> <li>W1-10 – Intersection in Curve</li> <li>W1-11 – Hairpin Curve</li> <li>W1-15 – 270 Degree Loop</li> <li>W2-1 – Cross Road</li> <li>W2-2, -3 – Side Road</li> <li>W2-4, -5 – T and Y Intersection</li> <li>W2-6 – Circular Intersection</li> </ul>	<ul style="list-style-type: none"> <li>W3-1 – Stop Ahead</li> <li>W3-2 – Yield Ahead</li> <li>W3-3 – Signal Ahead</li> <li>W4-1 – Merge</li> <li>W4-2 – Lane Ends</li> <li>W4-3 – Added Lane</li> <li>W4-5 – Entering Roadway Merge</li> <li>W4-6 – Entering Roadway Added Lane</li> <li>W6-1, -2 – Divided Highway Begins and Ends</li> <li>W6-3 – Two-Way Traffic</li> <li>W10-1, -2, -3, -4, -11, -12 – Highway-Railroad Advance Warning</li> </ul>	<ul style="list-style-type: none"> <li>W11-2 – Pedestrian Crossing</li> <li>W11-3 – Deer Crossing</li> <li>W11-4 – Cattle Crossing</li> <li>W11-5 – Farm Equipment</li> <li>W11-6 – Snowmobile Crossing</li> <li>W11-7 – Equestrian Crossing</li> <li>W11-8 – Fire Station</li> <li>W11-10 – Truck Crossing</li> <li>W12-1 – Double Arrow</li> <li>W16-5p, -6p, -7p – Pointing Arrow Plaques</li> <li>W20-7a – Flagger</li> <li>W21-1 and W21-1a – Worker</li> </ul>
--	--	--

#### Fine Symbol Signs – Symbol signs not listed as Bold Symbol Signs.

#### Special Cases

<ul style="list-style-type: none"> <li>W3-1 – Stop Ahead: red retroreflectivity <math>\geq 7</math></li> <li>W3-2 – Yield Ahead: red retroreflectivity <math>\geq 7</math>; white retroreflectivity <math>\geq 35</math></li> <li>W3-3 – Signal Ahead: red retroreflectivity <math>\geq 7</math>; green retroreflectivity <math>\geq 7</math></li> <li>W3-5 – Speed Reduction: white retroreflectivity <math>\geq 50</math></li> <li>For non-diamond-shaped signs such W14-3 (No Passing Zone), W4-4p (Cross Traffic Does Not Stop), or W13-1, -2, -3, -5 (Speed Advisory Plaques), use largest sign dimension to determine proper minimum retroreflectivity level</li> </ul>
---

68 Support:  
69 03 Compliance with the Standard in Paragraph 2 is achieved by having a method in place  
70 and using the method to maintain the minimum levels established in Table 2A-3.  
71 Provided that an assessment or management method is being used, an agency or official  
72 having jurisdiction would be in compliance with the Standard in Paragraph 2 even if there  
73 are some individual signs that do not meet the minimum retroreflectivity levels at a  
74 particular point in time.

75 *Guidance:*  
76 04 *Except for those signs specifically identified in Paragraph 6, one or more of the*  
77 *following assessment or management methods should be used to maintain sign*  
78 *retroreflectivity:*

- 79 A. *Visual Nighttime Inspection*—*The retroreflectivity of an existing sign is assessed*  
80 *by a trained sign inspector conducting a visual inspection from a moving vehicle*  
81 *during nighttime conditions. Signs that are visually identified by the inspector to*  
82 *have retroreflectivity below the minimum levels should be replaced.*
- 83 B. *Measured Sign Retroreflectivity*—*Sign retroreflectivity is measured using a*  
84 *retroreflectometer. Signs with retroreflectivity below the minimum levels should*  
85 *be replaced.*
- 86 C. *Expected Sign Life*—*When signs are installed, the installation date is labeled or*  
87 *recorded so that the age of a sign is known. The age of the sign is compared to*  
88 *the expected sign life. The expected sign life is based on the experience of sign*  
89 *retroreflectivity degradation in a geographic area compared to the minimum*  
90 *levels. Signs older than the expected life should be replaced.*
- 91 D. *Blanket Replacement*—*All signs in an area/corridor, or of a given type, should be*  
92 *replaced at specified intervals. This eliminates the need to assess retroreflectivity*  
93 *or track the life of individual signs. The replacement interval is based on the*  
94 *expected sign life, compared to the minimum levels, for the shortest-life material*  
95 *used on the affected signs.*
- 96 E. *Control Signs*—*Replacement of signs in the field is based on the performance of a*  
97 *sample of control signs. The control signs might be a small sample located in a*  
98 *maintenance yard or a sample of signs in the field. The control signs are*  
99 *monitored to determine the end of retroreflective life for the associated signs. All*  
100 *field signs represented by the control sample should be replaced before the*  
101 *retroreflectivity levels of the control sample reach the minimum levels.*
- 102 F. *Other Methods*—*Other methods developed based on engineering studies can be*  
103 *used.*

104 Support:  
105 05 Additional information about these methods is contained in the 2007 Edition of FHWA's  
106 "Maintaining Traffic Sign Retroreflectivity" (see Section 1A.11).

107 Option:  
108 06 Highway agencies may exclude the following signs from the retroreflectivity  
109 maintenance guidelines described in this Section:

- 110 A. Parking, Standing, and Stopping signs (R7 and R8 series)  
111 B. Walking/Hitchhiking/Crossing signs (R9 series, R10-1 through R10-4b)  
112 C. Acknowledgment signs  
113 ~~D. All signs with blue or brown backgrounds~~  
114 D. Bikeway signs that are intended for exclusive use by bicyclists or pedestrians

115

116

117

118 RWSTC Vote: For: Unanimous 1-8-14

119 Against:

120 Abstentions:

121

122 Council Vote: For: 1-10-14 Unanimous

123 Against:

124 Abstentions:

125

126 c: NCUTCD/Jan 2014/Heydel/ RW # 2 - Table 2A-3 added sheeting types, 5-11-

127 13, approved by RWSTC 6-26-13 revised following sponsor comments 12-15-13, revised

128 12-16-13, approved by RWSTC 1-8-14, approved by Council 1-10-14

129