

2 3

4

5 6

7 8

9

10

11

12 13

14

15

16 17

18 19

20

21

22

23

24

25 26

27

National Committee on **Uniform Traffic Control Devices**

12615 West Keystone Drive * Sun City West, AZ, 85375 Telephone (623)680-9592 * e-mail: ncutcd@aol.com

Attachment No. 1 Item No.: 16A-RW-01

NCUTCD Proposal for Changes to the **Manual on Uniform Traffic Control Devices**

TECHNICAL Regulatory & Warning Signs Committee

COMMITTEE:

ITEM NUMBER: 16A-RW-01 **TOPIC:** Parking Signs

ORIGIN OF REQUEST: RWSTC Task Force: Tom Heydel (RWSTC Chair), Mark

Bott, Bob Canfield, Richard Meredith, Lee Roadifer, Randy

McCourt, Ross Oven, Dave Woosley

AFFECTED SECTIONS

OF MUTCD:

Sections 2B.46, 2B.47 and 2B.48, 2B.49

DEVELOPMENT HISTORY:

Approved by Technical Committee: 01/07/2016

• Approved by Technical Committee following Sponsor comments: 06/08/2016

• Approved by NCUTCD Council: 06/10/2016

This is a proposal for recommended changes to the MUTCD that has been approved by the NCUTCD Council. This proposal does not represent a revision of the MUTCD and does not constitute official MUTCD standards, guidance, or options. It will be submitted to FHWA for consideration for inclusion in a future MUTCD revision. The MUTCD can be revised only through the federal rulemaking process.

SUMMARY:

The management of parking has become a more complex issue than in the past with increasing needs for curb space to be utilized in various ways as communities' needs change. Figure 1 shows several examples of multiple parking restrictions or regulation for one curb area. While dramatic in this case of over a dozen (in Culver City, CA), sign messages managing the use of curb space for different time periods and days of the week is not uncommon.

The use of parking control signs generally falls into two groups: signs used to facilitate roadway operations and safety, and signs used to manage the use of areas where parking is allowed.

- 28 Operational and safety uses can include No Parking, No Stopping or Standing, Bus Zones, Tow-
- 29 Away zone, street sweeping, snow, fire lanes, etc. These signs may require an engineering study 30 to determine placement, such as at intersections for keeping the sight triangle clear or facilitate
- 31 turning movements. Parking or curb space management covers all the differing ways of dealing
- 32 with the space beyond that needed for operations and safety, where an engineering review
- 33 determines there is adequate space to safely park. Non-operational signs deal with time

restrictions, paid parking, loading space for persons with disabilities, electric vehicle charging, residential permits, special events, motorcycle parking, bicycle parking, police/government vehicles, taxi stands (vehicle, pedicab, horse drawn), valet parking, emergency parking, car sharing, carpools, and others.

Additionally, the need to instruct drivers how to park is not uncommon (angled parking, parallel parking, back in parking, etc). Local jurisdictions have codes, ordinances, and regulations that sometimes affect sign designs and layouts. As a result the MUTCD continues to expand to cover all these different types, styles, sizes, number and messaging of parking signs. Many of the signs shown in Figure 1 do not meet MUTCD. The signs shown below are intended to show how parking signs can proliferate and do not meet MUTCD in terms of color, text size, etc.





49 Figure 1 (part 1)





Figure 1 (part 2)

DISCUSSION

 In order to avoid the continuing expansion of the MUTCD for individual parking signs, it is more desirable to have the MUTCD provide the function, shape, color, size, spacing and retroreflectivity requirements rather than to show all the possible parking sign messages that could be used. Therefore, the number of sign designation numbers shown has been reduced to reflect only a sampling of sign messages.

The Synthesis of signs done by FHWA in 2005 provided for the parking signs that are commonly used which resulted in the Pay to Park series of signs. However, since then there has been a continual increase in the types of parking signs being used.

Streamlining the MUTCD text and sign details associated with parking signs provides the user the regulation requirements without covering every possible message that could be used on a parking sign.


RECOMMENDED MUTCD CHANGES

The following present the proposed changes to the current MUTCD within the context of the current MUTCD language. Proposed additions to the MUTCD are shown in blue underline and proposed deletions from the MUTCD are shown in red strikethrough. Changes previously approved by NCUTCD Council (but not yet adopted by FHWA) are shown in green double underline for additions and green double strikethrough for deletions. In some cases, background comments may be provided with the MUTCD text. These comments are indicated by [highlighted light blue in brackets].

Part 2. SIGNS

```
7. NO PARKING BUS STOP (R7-7, R7-107, R7-107a):
123
         8. RESERVED PARKING for persons with disabilities (R7-8):
124
125
         9. VAN ACCESSIBLE (R7-8P):
126
         10. Pay Station (R7-20);
         11. Pay Parking (R7-21, R7-21a, R7-22);
127
         12. Parking Permitted X:XX AM TO X:XX PM (R7-23);
128
129
         13. Parking Permitted XX HOUR(S) XX AM – XX PM (R7-23a);
130
         14. XX HR PARKING X:XX AM TO X:XX PM (R7-108);
131
         15. NO PARKING ANYTIME/XX HOUR PARKING X:XX AM — X:XX PM (R7-200, R7-
132
            200a);
133
         16. TOW-AWAY ZONE (R7-201P, R7-201aP);
134
         17. THIS SIDE OF SIGN (R7-202P);
         18. EMERGENCY SNOW ROUTE NO PARKING IF OVER XX INCHES (R7 203);
135
136
         19. NO PARKING ON PAVEMENT (R8-1);
137
         20. NO PARKING EXCEPT ON SHOULDER (R8-2);
138
         21. No Parking (R8-3, R8-3a);
139
         22. EXCEPT SUNDAYS AND HOLIDAYS (R8-3bP);
140
         23. ON PAVEMENT (R8-3cP);
141
         24. ON BRIDGE (R8-3dP);
142
         25. ON TRACKS (R8-3eP);
143
         26. EXCEPT ON SHOULDER (R8-3fP);
144
         27. LOADING ZONE (R8-3gP);
145
         28. X:XX AM TO X:XX PM (R8-3hP);
146
         29. EMERGENCY PARKING ONLY (R8-4);
147
         30. NO STOPPING ON PAVEMENT (R8-5);
148
         31. NO STOPPING EXCEPT ON SHOULDER (R8-6); and
149
         32. EMERGENCY STOPPING ONLY (R8-7).
```


Figure 2B-24 Parking and Standing Signs and Plaques (R7 Series)



NOTE: Moved these signs to new figures 2B-24a and Figure 2B-25a separating restriction parking signs from permitted parking signs. Deleted some of these signs. See

ne w figure 2B-24a and 2B-25a

Figure 2B-25 Parking and Stopping Signs and Plaques (R8 Series)



Move these signs to new figures 2B-24a and 2B-24b separating restriction parking signs and emergency restriction signs. Also, deleted some of these signs. See new figure 2B-24a and 2B-24b

153154

155

151

152

Section 2B.47 Design of Parking, Standing, and Stopping Signs

- 156 Support:
- 157 of Discussions of parking signs and parking regulations in this Section apply not only to parking, but also
- 158 to standing and stopping.
- 159 **Standard:**
- 160 of Parking, Standing or Stopping signs shall be rectangular or square.
- 161 02 The symbol "P" for parking prohibition, restriction or limitation signs shall be black.
- 162 03 Parking Restriction signs (See Figure 2B-24a for some commonly used examples) shall
- be used where parking is prohibited at all times or at specific times, and shall have red
- legend and border on a white background, except that the R8-3 and R7-107a sign shall
- have a black border and a red circle and slash on a white background.
- 166 03a Public Agencies shall follow established law (state law, local ordinance, or regulation)
- as adopted by the authorized agency regarding what messages are allowed on parking
- 168 **signs**.
- 169 Option:
- 170 03b The words PARKING or NO PARKING may be used as an alternative to the PARKING or
- No Parking symbol (see R7 -2 sign in Figure 2B-24a) Moved from paragraph 19 to here since
- it applies to paragraph 02.
- 173 04 The R7-201P sign may have a black or red symbol and border on a white background.




Figure 2B-24b Emergency Restriction Signs



Standard:

 os Permitted Parking signs or signs that limit how parking is allowed shall be used where limited-time parking or parking in a particular manner is permitted or limited. These signs and shall have a green legend and border on a white background. (See Figure 2B-25a for some commonly used examples)

Figure 2B-25a Examples of Permitted and Limited Parking Signs





R7-24 R7-25

Add R7-24 and R7-25 sign to Figure 2B-25a previously approved by Council, January 2014, RW # 5, RESERVED PARKING CHARGING ONLY sign

62 06 The legend on parking signs shall state applicable regulations. Parking signs (see Figures 2B-24a and 2B-25a) shall comply with the standards of shape, color, and location.

03 Where parking is prohibited at all times or at specific times, the basic design for parking signs shall have a red legend and border on a white background (Parking Prohibition signs), except that the R8-4 and R8-7 signs and the alternate design for the R7-201aP plaque shall have a black legend and border on a white background, and the R8-3 sign shall have a black legend and border and a red circle and slash on a white background. (NOTE: Moved to paragraph 03 above and modified.)

04 Where only limited-time parking or parking in a particular manner are permitted, the signs shall have a green legend and border on a white background (Permissive Parking signs). (NOTE: Moved to paragraph 05 above and modified)

Guidance:

95 07 Parking signs should display the following information from top to bottom of the sign, in the order listed:

A. Any tow-away message or symbol.

B. A The restriction or prohibition;

C.B The times of the day that it is applicable, if not at all hours; and

- 219 D.C The days of the week that it is applicable, if not every day.
- 220 E. Qualifying or supplementary information.
- *F. Exemptions to the restriction or prohibition.*
- 222 Option:
- 223 08 A tow away message or symbol may be installed at the bottom.
- 224 Guidance:
- 225 of the parking restriction applies to a limited area or zone, the limits of the restriction should
- be shown by arrows or supplemental plaques. If arrows are used and if the sign is at the end of
- a parking zone, there should be a single-headed arrow pointing in the direction that the
- 228 regulation is in effect. If the sign is at an intermediate point in a zone, there should be a double
- 229 headed arrow pointing both ways. When a single sign is used at the transition point between two
- 230 parking zones, it should display a right and left arrow pointing in the direction that the
- 231 respective restrictions apply.
- 232 **Standard:**
- 233 09a The times and days for which regulations, restrictions, permitted or limited uses or pay
- parking are in effect shall be posted if they are not in effect at all times of day or all days of
- 235 the week.
- 236 Guidance:
- 237 *OBS* The time restrictions should also be visible to a pedestrian.
- 238 Option:
- 239 <u>Ho 10</u> As an alternate to the use of arrows to show designated restriction zones, word messages
- such as BEGIN, END, HERE TO CORNER, HERE TO ALLEY, THIS SIDE OF SIGN, or
- 241 BETWEEN SIGNS may be used. (NOTE: This paragraph moved from paragraph 10 in
- 242 MUTCD to here.)
- 243 07 Where special parking restrictions are imposed during heavy snowfall, Emergency Snow
- 244 Route (R7-203) signs (see Figure 2B-24) should be installed. The legend will vary according to
- 245 the regulations, but the signs should be vertical rectangles, having a white background with the
- 246 upper part of the plate a red background.
- 247 If the sign is at an intermediate point in a zone, there may be a double-headed arrow pointing
- both ways.
- 249 <u>12</u> To minimize the number of parking signs, Bblanket regulations that apply to a given district
- 250 may, if legal, be posted at district boundary lines.
- 251 13 If a roadway has an adjacent paved shoulder, the legend NO PARKING EXCEPT ON
- 252 SHOULDER or NO STOPPING EXCEPT ON SHOULDER may be used. The R8-3 symbol
- sign or the word message NO PARKING may be used to prohibit any parking along a roadway.
- Word message supplemental plaques may be mounted below NO PARKING signs. These word
- 255 message supplemental plaques may include but not be limited to legends such as EXCEPT
- 256 SUNDAYS AND HOLIDAYS, ON PAVEMENT, ON BRIDGE, ON TRACKS. EXCEPT ON
- 257 SHOULDERS, LOADING ZONE, and X:XX AM TO X:XX PM
- 258 Guidance:
- 260 Route (R7-203) signs (see Figure 2B-24a) should be installed. The legend will vary according to
- 261 the regulations, but the signs should be vertical rectangles, having a white background with the

- 262 upper part of the plate a red background. (Note: this paragraph moved from Paragraph 07 in
- 263 2009 MUTCD to here.)
- 264 <u>46 15</u> If a fee is charged for <u>on-street</u> parking and a midblock <u>or end of block</u> pay station is used
- instead of individual parking meters for each parking space, pay parking signs should be used.
- 266 <u>Pay Parking (R7-21 through R7-22) (R7-22) signs</u> (see Figure 2B-24-25a) should be used to
- 267 define the area where the pay station parking applies. Pay Station (R7-20) signs (see Figure 2B-
- 268 24 25a) should be used at the pay station or to direct road users to the pay station. (Note: This
- paragraph moved from paragraph 16 of 2009 MUTCD to here. Items shown in green text
- 270 Previously Approved by Council January 2012, RW # 5
- 271 **Standard:**
- 273 accommodate wheelchair vans, a VAN ACCESSIBLE (R7-8P) plague shall be mounted
- 274 below the R7-8 sign. The R7-8 sign (see Figure 2B-24) shall have a green legend and
- 275 border and a white wheelchair symbol on a blue square, all on a white background. The
- 276 R7-8P plaque (see Figure 2B-24) shall have a green legend and border on a white
- 277 background. (NOTE: This paragraph moved to paragraph 16 below)
- 278 Option:
- 279 on To minimize the number of parking signs, blanket regulations that apply to a given district
- 280 may, if legal, be posted at district boundary lines. (NOTE: This paragraph moved to paragraph
- 281 11 above and modified)
- 282 10 As an alternate to the use of arrows to show designated restriction zones, word messages such
- 283 as BEGIN, END, HERE TO CORNER, HERE TO ALLEY, THIS SIDE OF SIGN, or
- 284 BETWEEN SIGNS may be used. (NOTE: This paragraph moved to paragraph 09 above)
- 285 **Standard:**
- 286 10 16 If the pay parking is subject to a maximum time limit, the appropriate time limit (number of
- hours or minutes) shall be displayed on the Pay Parking (R7-21 or R7-21a) and Pay Station (R7-20)
- signs. (Note: This paragraph moved from paragraph 17 in 2009 MUTCD to here)
- 289 17 Where parking spaces that are reserved for persons with disabilities are designated to
- accommodate wheelchair vans, a VAN ACCESSIBLE (R7-8P) plaque shall be mounted below the
- R7-8 sign. The R7-8 sign (see Figure 2B-24-25a) shall have a green legend and border and a white
- wheelchair symbol on a blue square, all on a white background. The R7-8P plaque (see Figure 2B-
- 293 24 25a) shall have a green legend and border on a white background. (Note: This paragraph 08 of
- 294 **2009 MUTCD moved to here.**)
- 295 Guidance:

- 296 Where parking spaces are reserved for charging electric vehicles, a RESERVED PARKING
- for charging electric vehicles-(R7-24) sign (see Figure 2B-24 25b) should be installed adjacent
- 298 to the designated space.
- 300 <u>19 Where on-street parking spaces are reserved for charging electric vehicles and have time</u>
- restrictions, XX HOUR Parking for charging electric vehicle (R7-25) sign (see Figure 2B-24
- 302 25b) should be installed adjacent to the designated space.
- Green Text previously approved by Council January 2014, RW # 5.
- 306 Option:

- 307 08 20 Where parking is prohibited during certain hours and time-limited parking or parking in a particular 308 manner allowed is permitted during certain other time periods, the red Parking Prohibition and green 309 Permissive Parking signs may be designed as follows:
 - A. Two 12 x 18-inch parking signs may be used with the red Parking Prohibition sign (R7-2) installed above or to the left of the green Permissive Parking sign (R7-5); or
 - B. The red Parking Prohibition sign (R7-12) and the green Permissive Parking sign (R7-5) may be combined (see Figure 2B 24) to form an R7 200 sign on a single 24 x 18 inch sign, or an R7 200a sign on a single 12 x 30 inch sign.
- 315 +2 21 At the transition point between two parking zones, a single sign or two signs mounted side by side 316 may be used.
- 317 13 The words PARKING or NO PARKING may be used as an alternative to the PARKING or No 318 Parking symbol (see R7 2 sign in Figure 2B 24a) This sentence moved to paragraph 03b above.
- 319 The supplemental educational plaque, NO PARKING, with a red legend and border on a white
- 320 background, may be used above signs incorporating the No Parking symbol.
- 321 14-22 Alternate designs for the R7-107 sign may be developed such as the R7-107a sign (see Figure 2B-
- 322 24a). Alternate designs may include, on a single sign, a transit logo, an approved bus symbol, a parking
- 323 prohibition, the words BUS STOP, and an arrow. The preferred bus symbol color is black, but other dark
- 324 colors may be used. Additionally, the transit logo may be displayed on the bus face in the appropriate
- 325 colors instead of placing the logo separately. The reverse side of the sign may contain bus routing
- 326 information.

311

312

313

314

- 327 23.15 To make the parking regulations more effective and to improve public relations by giving a definite
- 328 warning, A a TOW-AWAY ZONE (R7-201P) plaque (see Figure 2B-24a) may be attached above or
- 329 below appended to, or the message incorporated in, any parking prohibition sign. The Tow Away Zone
- 330 (R7 201aP) symbol plague may be used instead of the R7 201P word message plague. The R7 201aP
- 331 plaque may have either a black or red legend and border on a white background. The word message Tow-
- 332 Away Zone may be used in lieu of the symbol.
- Guidance: 333
- 334 20 16 If a fee is charged for parking and a midblock pay station is used instead of individual parking
- 335 meters for each parking space, pay parking signs should be used. Pay Parking (R7-22) signs (see Figure
- 336 2B-24-25a) should be used to define the area where the pay station parking applies. Pay Station (R7-20)
- 337 signs (see Figure 2B 24 25a) should be used at the pay station or to direct road users to the pay station.
- 338 This paragraph is moved above to paragraph 14.
- 340 **Standard:**

- 341 17 If the pay parking is subject to a maximum time limit, the appropriate time limit (number of
- 342 hours or minutes) shall be displayed on the Pay Parking (R7-21 or R7-21a) and Pay Station (R7-20)
- 343 signs. This paragraph moved to paragraph 15 above.
- 344 Option:
- 345 48 In rural areas (see Figure 2B-25), Tthe legends NO PARKING ON PAVEMENT (R8-1) or NO
- 346 STOPPING ON PAVEMENT (R8 5) are generally suitable and may be used. If a roadway has paved
- shoulders, the NO PARKING EXCEPT ON SHOULDER sign (R8-2) or the NO STOPPING EXCEPT 347
- 348 ON SHOULDER sign (R8-6) may be used as these signs would be less likely to cause confusion. The
- 349 R8 3 symbol sign or the word message NO PARKING (R8 3a) sign may be used to prohibit any parking
- 350 along a given highway. Word message supplemental plaques may be mounted below NO PARKING
- 351 signs the R8 3 or R8 3a sign. These word message supplemental plaques may include legends such as
- EXCEPT SUNDAYS AND HOLIDAYS (R8 3bP), ON PAVEMENT (R8 3cP), ON BRIDGE (R8 3dP), 352
- 353 ON TRACKS (R8 3eP), EXCEPT ON SHOULDERS (R8 3fP), LOADING ZONE (with arrow) (R8-

- 354 3gP), and X:XX AM TO X:XX PM (with arrow) (R8 3hP). (Note: This paragraph moved above to
- paragraph 12 and edited.
- 24 19 Colors that are in compliance with the provisions of Section 2A.10 may be used for color
- 357 coding of parking time limits. The Pay Station (R7-20) sign may contain colors other than green
- 358 <u>for color coding the parking time limit portion of the sign only.</u> Green text_previously approved
- by Council in January 2012, RW # 5
- 360 Guidance:
- 361 <u>25-20</u> *If colors are used for color coding of parking time limits, the colors green, red, and black*
- 362 should be the only colors that are used, Green Text previously approved by Council on
- 363 January 19, 2012, RW # 5
- 364 26 Lettering height and symbols size should be based upon the FHWA Standard Highway Signs and
- 365 Markings Book. NOTE: The most commonly used designs should be retained in the Standard Highway
- 366 Signs and Marking Manual.

Section 2B.48 Placement of Parking, Stopping, and Standing Signs

- 369 Guidance:
- 370 01 When signs with arrows are used to indicate the extent of the restricted zones, the signs should be set at
- an angle of not less than 30 degrees or more than 45 degrees with the line of traffic flow in order to be
- 372 *visible to approaching traffic.*
- 373 02 Spacing of signs should be based on legibility and sign orientation.
- 374 03 If the zone is unusually long, signs showing a double arrow should be used at intermediate points
- 375 *within the zone.*
- 376 **Standard:** Option
- 377 04 If the signs are mounted at an angle of 90 degrees to the curb line, two signs may shall be mounted
- back to back at the transition point between two parking zones, each with an appended THIS SIDE OF
- 379 SIGN (R7-202P) supplemental plaque.
- 380 Guidance:
- 381 05 If the signs are mounted at an angle of 90 degrees to the curb line, signs without any arrows or
- appended plagues should be used at intermediate points within a parking zone, facing in the direction of
- approaching traffic. Otherwise the standards of placement should be the same as for signs using
- 384 directional arrows.

385386

Section 2B.49 Emergency Restriction Signs (R8-4, R8-7, R8-8)

- 387 Option:
- 388 of The EMERGENCY PARKING ONLY (R8-4) sign (see Figure 2B-25-24b) or the
- 389 EMERGENCY STOPPING ONLY (R8-7) sign (see Figure 2B-25 24b) may be used to
- discourage or prohibit shoulder parking, particularly where scenic or other attractions create a
- tendency for road users to stop temporarily.
- 392 02 The DO NOT STOP ON TRACKS (R8-8) sign (see Figure 8B-1) may be used to discourage
- or prohibit parking or stopping on railroad or light rail transit tracks (see Section 8B.09).
- 394 **Standard:**
- 395 03 Emergency Restriction signs shall be rectangular and shall have a red or black legend and
- 396 border on a white background.

MODIFY Table 2B-1 to eliminate parking signs no longer shown.

398

 $C: ncut cd/January\ 2016/16A-RW-01/parking\ signs\ Sections\ 2B.46,\ 2B.47,\ 2B.48,\ and\ 2B.49\ 11-15-15,\ revised\ 11-22-15,\ revised\ 11-27-15,\ revised\ 12-15-15,\ revised\ 12-12-15,\ revised\ 12-23-15,\ revised\ 12-23-15,\ revised\ 12-26-15,\ revised\ 12-26-1$